



# BS80 Piranha II 2D

General Purpose Handheld Scanners

|   |   |   |   |   |   |
|---|---|---|---|---|---|
|  |  |  |  |  |  |
| 1.2m drop   | 1D & 2D   | Bluetooth 4.0   | CMOS  | EasySet   | IP42  |
|  |  |  |   |   |   |
| Laser aimer   | Megapixel   | Warranty 3 Years  |   |   |   |



## Features

### Superior Reading Performance

The BS80 Piranha II is offered in 2 versions, containing a 1D or a 1D+2D barcode scanning engine. Both of these engines read virtually any barcode from paper or screen. The 2D device has been equipped with a laser aimer with a red cross to make barcode reading easier and faster.

### Easy Bluetooth Pairing

With Bluetooth 4.0 wireless technology, the BS80 Piranha II enables effortless pairing to any Android, iOS, or Windows device, making it simple and convenient for users to transmit data.

### Seamless Barcode Capture and Storage

Offering versatile barcode scanning capabilities, the BS80 Piranha II enables fast real-time scanning with seamless data transfer to the host via Bluetooth. However, users can also take advantage of the 1MB memory when operating in batch collection mode, which can store thousands of barcodes offline for subsequent download via Bluetooth or cable.

### Edits On the Go

The BS80 Piranha II boasts not only a reliable scan button but also two extra buttons for convenient data editing. For data collection mode, the Delete button allows users to quickly rectify scanning errors by deleting the last scanned barcode. Meanwhile, the Function button serves as a virtual keyboard recall feature, enabling manual data input on a wide range of host devices, including iOS products. This makes the BS80 Piranha II an ideal companion for all your data collection needs.

### Versatile Charging & Communication

The BS80 Piranha II features a fast and reliable USB-C port that can be used both for charging and establishing a connection to a host to download data or access the EasySet configuration software. In addition, the device also supports the use of pogo pins to charge via the cradle.

**3** Years Full Warranty



## TECHNICAL SPECIFICATIONS

# BS80 Piranha II 2D

### Data Capture

|                                 |  |
|---------------------------------|--|
| 1D                              | All major 1D symbologies, including Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, ISSN, Interleaved 2 of 5, ISBN, Code 93, UCC/EAN-128, GS1 Databar, etc. |
| 2D                              | All major 2D symbologies, including PDF417, QR Code, Data Matrix, etc.   |
| Depth of Field Code 128 (10mil) | 38 mm - 411 mm   |
| Depth of Field Code 39 (5mil)   | 65 mm - 260 mm   |

|                                   |                 |
|-----------------------------------|-----------------|
| Depth of Field DataMatrix (10mil) | 40 mm - 250 mm  |
| Depth of Field EAN 13 (13mil)     | 50 mm - 540 mm  |
| Depth of Field QR (15mil)         | 20 mm - 320 mm  |
| Image Sensor                      | 1280 x 800 CMOS |
| Minimal Print Contrast            | 20%             |
| Resolution                        | ≥5mil           |
| Scan Angle Pitch                  | ±60°            |
| Scan Angle Roll                   | 360°            |
| Scan Angle Skew                   | ±60°            |

### Physical

|                          |  |
|--------------------------|--|
| Battery Type             | 3.7 V, 900 mA, Rechargeable Li-ion battery         |
| Current @ 5VDC Operating | 280 mA (Bluetooth is on)                           |
| Current @ 5VDC Standby   | 11 mA  |
| Dimensions               | 88(W) × 46(D) × 24.5(H) mm                         |
| Expected Battery Life    | 5 hours of continuous operation (scan once per 6s) |
| Interfaces               | USB-C  |
| Notifications            | Beep, LED, Vibration                               |
| Weight                   | 63 g   |

### Wireless

|                           |   |
|---------------------------|---|
| Radio Technology          | 2.4 - 2.5 GHz ISM band, compatible with Bluetooth 4.0/3.0/2.1+EDR |
| Wireless Distance ( max.) | 50 m (open space)   |

### Environmental

|                                |  |
|--------------------------------|--|
| Charge Temperature             | 0°C to 45°C (32°F to 113°F)                      |
| Drop                           | 1.2 m  |
| Electro Static Discharge (ESD) | ±12 kV (air discharge), ±4 kV (direct discharge) |
| Humidity                       | 5% to 95% (non-condensing)                       |
| IP Rating                      | IP42   |
| Operating Temperature          | -20°C to 50°C (-4°F to 122°F)                    |
| Storage Temperature            | -40°C to 70°C (-40°F to 158°F)                   |

### Software

|                     |         |
|---------------------|---------|
| Configuration Tools | EasySet |
|---------------------|---------|

### Certifications

|                         |   |
|-------------------------|---|
| Certifications Hardware | FCC, CE RED, IEC 60825, IEC 62471, RoHS, CE UK, TELEC |
|-------------------------|---|

### Warranty

|                                |                  |
|--------------------------------|------------------|
| Comprehensive Service Contract | 3 Years, 5 Years |
| Warranty Extension             | +2 Years         |
| Warranty Standard              | 3 Years          |

### Accessories

|                      |  |
|----------------------|--|
| Accessories Optional | Charging cradle, Fast charging power adapter |
|----------------------|--|

What's in the box?

|               |                              |
|---------------|------------------------------|
| NLS-BS8080-2D | BS80 Piranha 2D, USB-C cable |
|---------------|------------------------------|

## Accessories

---

Charging/Power

AD60-D-M Power Supply with Multiplug Adapter (AD60-D-M)  
ADP710 Power Supply for Mobile Computers (ADP710)

---



**Newland AIDC EMEA**

Feel free to contact us or a partner near you.  
[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice  
© Newland AIDC EMEA 2026 - All rights reserved