



# FM515-H

Industrial Fixed-Mount



1D



CCD



High motion tolerance



IP54



RS232



Warranty 2 Years



Wide Scan Angle



Wide Voltage 5-24V



## Features

### Tailored for Laboratory Applications

With its wide scan angle, the FM515-H is perfectly suited for laboratories where scanning lengthy 1D barcodes is a common challenge. The FM515-H provides a versatile depth of field, covering standard distances from 35mm to 190mm, enabling you to efficiently scan up to eight rows of lab vials from a fixed position.

### Fast Scanning for Higher Productivity

Elevate your data collection efficiency with the FM515-H, boasting a remarkable scanning speed of 780 scans per second. The FM515-H empowers you to speed up track and trace processes and handle a greater number of samples. It is the go-to choice for critical applications in in-vitro diagnostics and laboratories, where speed is pivotal for precise and timely results.

### Built to Last

The FM515-H is housed in a robust IP54-sealed casing, designed to withstand the rigorous demands of laboratory environments and ensure the durability of your equipment.

### Flexible Vertical and Horizontal Configurations

The FM515 Series offers adaptability with both vertical and horizontal configurations. These choices seamlessly integrate into existing laboratory setup and equipment, ensuring optimal utilization of scanning technology within a workspace.

### Wide Voltage Range

The FM515-H features an extensive input voltage range from 5 to 24VDC, offering adaptability to various power sources and global electrical standards. This versatility ensures stable and reliable operation without the need for additional power converters.

**2** Years Full Warranty



## TECHNICAL SPECIFICATIONS

### FM515-H

#### Data Capture

1D	All major 1D symbologies
Beam Exit	Scan window with front beam exit
Depth of Field	35 mm - 190 mm

Field of View Horizontal	68°
Illumination	Red LED (615nm)
Image Sensor	2500 CCD
Minimal Print Contrast	25%
Resolution	≥6mil
Scan Rate	780 scans per second

#### Physical

Current @ 24VDC Operating	150 mA RMS (typical); 250 mA (max)
Current @ 5VDC Operating	737 mA RMS (typical); 870 mA (max)
Dimensions	62.5(W) × 50.5(D) × 21.5(H) mm
Housing	Aluminium
Input Voltage	5-24 VDC ±5%
Interfaces	RS-232
Notifications	Status indicator
Power Consumption	< 4W
Weight	166 g

#### Environmental

Ambient Light	≤5000 lux
Humidity	5% to 95% (non-condensing)
IP Rating	IP54
Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)

#### Software

Configuration Tools	EasySet
---------------------	---------

#### Certifications

Certifications Hardware	FCC, IEC 62471, CE, RoHS 2.2, UL
-------------------------	----------------------------------

#### Warranty

Warranty Standard	2 Years
-------------------	---------



#### Newland AIDC EMEA

Feel free to contact us or a partner near you.

[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved